

## KILNS FOR GLASS

### ELECTRIC KILNS FOR GLASS CASTING

kiln model	operational temperature	inner volume (l)	inner dimensions (mm)			outer dimensions (mm)			heating power	voltage	price
			width	length	height	width	length	height			
KSP 60	1100 °C	52	370	350	400	730	840	1680	5,2 kW	3 x 400 V	6 430 €
KSP 130	1100 °C	118	470	500	500	820	950	1680	9 kW	3 x 400 V	7 360 €
KSP 180	1100 °C	175	530	550	600	920	1090	1680	12 kW	3 x 400 V	9 150 €
KSP 250	1100 °C	245	680	530	680	1100	1090	1780	14 kW	3 x 400 V	11 630 €
KSP 300	1100 °C	301	680	650	680	1100	1240	1780	17 kW	3 x 400 V	12 590 €
KSP 400	1100 °C	395	780	650	780	1200	1240	1880	21 kW	3 x 400 V	14 460 €
KSP 550	1100 °C	575	840	720	950	1300	1330	1980	27 kW	3 x 400 V	17 260 €
KSP 750	1100 °C	739	840	800	1100	1300	1410	1980	30 kW	3 x 400 V	19 990 €
KSP 1000	1100 °C	993	1040	830	1150	1500	1440	1980	39 kW	3 x 400 V	23 910 €
KSP 1100	1100 °C	1112	1040	930	1150	1500	1540	1980	42 kW	3 x 400 V	25 960 €
KSP 1400	1100 °C	1380	1290	930	1150	1750	1540	1980	48 kW	3 x 400 V	27 980 €
KSP 1600	1100 °C	1610	1290	1040	1200	1750	1650	1980	52 kW	3 x 400 V	29 930 €
KSP 1900	1100 °C	1920	1290	1240	1200	1750	1850	1980	58 kW	3 x 400 V	32 630 €
KSP 2100	1100 °C	2167	1290	1400	1200	1750	2000	1980	58 kW	3 x 400 V	34 910 €
KSP-2-1650	1100 °C	1664	1040	1600	1000	1500	2200	1980	58 kW	3 x 400 V	36 480 €
KSP-2-2000	1100 °C	1976	1040	1900	1000	1500	2500	1980	64 kW	3 x 400 V	40 450 €
KSP-2-2200	1100 °C	2184	1040	2100	1000	1500	2700	1980	68 kW	3 x 400 V	44 290 €

### ELECTRIC KILNS FOR DECORATION FIRING

kiln model	operational temperature	inner volume (l)	inner dimensions (mm)			outer dimensions (mm)			heating power	voltage	price
			width	length	height	width	length	height			
KSD 60	600 °C	55	390	350	400	730	840	1680	5,2 kW	3 x 400 V	6 600 €
KSD 130	600 °C	130	490	500	530	820	950	1680	9 kW	3 x 400 V	7 690 €
KSD 180	600 °C	182	550	550	600	920	1090	1680	12 kW	3 x 400 V	11 760 €
KSD 250	600 °C	252	700	530	680	1100	1090	1780	14 kW	3 x 400 V	12 090 €
KSD 300	600 °C	309	700	650	680	1100	1240	1780	17 kW	3 x 400 V	13 290 €
KSD 400	600 °C	406	800	650	780	1200	1240	1880	21 kW	3 x 400 V	16 350 €
KSD 500	600 °C	505	800	810	780	1200	1400	1880	24 kW	3 x 400 V	18 360 €
KSD 650	600 °C	675	900	750	1000	1300	1330	1980	27 kW	3 x 400 V	21 540 €
KSD 850	600 °C	859	900	830	1150	1300	1410	1980	30 kW	3 x 400 V	24 490 €
KSD 1150	600 °C	1135	1100	860	1200	1500	1440	1980	39 kW	3 x 400 V	28 410 €
KSD 1250	600 °C	1267	1100	960	1200	1500	1540	1980	42 kW	3 x 400 V	30 050 €
KSD 1550	600 °C	1555	1350	960	1200	1750	1540	1980	48 kW	3 x 400 V	33 390 €
KSD 1800	600 °C	1806	1350	1070	1250	1750	1650	1980	52 kW	3 x 400 V	35 960 €
KSD 2150	600 °C	2143	1350	1270	1250	1750	1850	1980	60 kW	3 x 400 V	39 260 €

### ELECTRIC KILNS FOR GLASS ANNEALING

kiln model	operational temperature	inner volume (l)	inner dimensions (mm)			outer dimensions (mm)			heating power	voltage	price
			width	length	height	width	length	height			
KSC 500	550 °C	574	700	820	1000	1200	1400	1960	14 kW	3 x 400 V	17 080 €
KSC 700	550 °C	722	800	820	1100	1300	1400	1960	17 kW	3 x 400 V	19 390 €
KSC 1000	550 °C	1056	800	1200	1100	1300	1800	1960	21 kW	3 x 400 V	23 340 €
KSC 1600	550 °C	1584	1200	1200	1100	1700	1800	1960	24 kW	3 x 400 V	25 940 €
KSC 2-1600	550 °C	1584	1650	800	1200	2150	1400	1960	24 kW	3 x 400 V	30 040 €
KSC 2000	550 °C	2160	1200	1500	1200	1700	2100	1960	30 kW	3 x 400 V	29 300 €
KSC 2-2500	550 °C	2376	1650	1200	1200	2150	1800	1960	34 kW	3 x 400 V	39 400 €
KSC 2-3700	550 °C	3762	1650	1900	1200	2150	2500	1960	38 kW	3 x 400 V	47 230 €

### ELECTRIC KILNS FOR TEMPERING AND MALLEABILIZING OF CRUCIBLES FOR GLASS

kiln model	operational temperature	inner volume (l)	inner dimensions (mm)			outer dimensions (mm)			heating power	voltage	price
			width	length	height	width	length	height			
KST 1000	1280 °C	700	1000	1000	1100	1500	1600	1960	34 kW	3 x 400 V	27 030 €
KST-C 1000	1280 °C	700	1000	1000	1100	1500	1600	1960	34 kW	3 x 400 V	35 530 €
KST 1500	1280 °C	900	1200	1200	1100	1700	1800	1960	40 kW	3 x 400 V	34 450 €
KST-C 1500	1280 °C	900	1200	1200	1100	1700	1800	1960	40 kW	3 x 400 V	42 510 €
KST 2000	1280 °C	1100	1400	1400	1100	1900	2000	1960	48 kW	3 x 400 V	38 050 €
KST-C 2000	1280 °C	1100	1400	1400	1100	1900	2000	1960	48 kW	3 x 400 V	48 830 €

NB: Price includes complete kiln in standard version including programmable controller, technical documentation, operating instructions, CE certificate.

Price excludes VAT of country of destination, transport, packaging and setting into operation.